



Lumistrips

DATASHEET

LUMIFLEX-RGBW-2080 OSRAM LED STRIP RGB-WHITE
5580LM 24V 120 LEDS/M 5M REEL


SKU: 39995



LUMIFLEX-RGBW-2080 OSRAM LED STRIP RGB-WHITE 5580LM 24V 120 LEDS/M 5M REEL

Article number (SKU)		38999		
Product name	LUMIFLEX-RGBW-2080 OSRAM LED STRIP RGB-WHITE 5580LM 24V 120 LEDS/M 5M REEL			
Classification	Professional			
Model identifier (equivalent models)	LumiFlex600 Pro RGB			
Photometric data (at TJ = 65°C, ± 10%)				
Light color	RED	GREEN	BLUE	WHITE
Binning	VJ - VX / EQ	BT - BV / DJ - 18	TX - UV / LS - S1	3-Step MacAdam
Color temperature (K)				4000 K
Dominant wavelength (nm)	616 - 626 nm	539 - 541 nm	464 - 477 nm	
Luminous flux (lm)	668 lm	1772 lm	460 lm	2680 lm
Luminous flux per meter (lm)	133 lm/m	354 lm/m	92 lm/m	536 lm /m
CRI (Ra)	-			80
Efficiency (lm/W)	30 - 137 lm/W			
Beam angle FWHP	120°			
Lifetime L80B10C1 (h)	>60000 h			
Photometric code	-			840/339
Electrical data (at TJ = 65°C, ± 10%) (reference settings)				
Operating mode	Constant voltage			
Voltage (V)	24 V			
Current (mA)	810 mA			
Power (W)	19.5 W per color, 78 W for RGBW			
Standby power consumption (W)	0 W			
Dimmable	Yes			
Dimensions / Mechanical data		Metric units	Imperial units	
Length	5000 mm	196.50"		
Width	10 mm	0.393"		
Height	2.67 mm	0.105"		
Number of LEDs (pcs)	600 pcs			
Weight (g)	80 g			
Heat dissipation	Yes			
Temperatures				
Operating temperature at Tc	-40 °C to +85 °C			
Ambient temperature	-40 °C to +50 °C			
Storage temperature	-40 °C to +100 °C			
Approvals / Certifications				
CE / RoHS / Reach	Yes			
EN 62471 Risk group	RG0			
Energy efficiency class	-			
Mains voltage luminous efficacy (lm/W)	-			
Version				
Date	1. Feb 2023			

LUMIFLEX-RGBW-2080 OSRAM LED STRIP RGB-WHITE 5580LM 24V 120 LEDS/M 5M REEL




WARRANTY INFO



This LED Strip has 5 years commercial warranty. Please refer to <https://www.lumistrips.com/lumistrips-en-warranty> for warranty terms.

MANUFACTURING INFO



This LED strip is **made in Germany**, at a flex production line that uses the innovative manufacturing technology of plasma direct metallization, to turn flexible substrates into electrical conductive and solderable circuit boards, even those that before have not been suitable for an assembly with electronic components.



LED strip made in reel-to-reel manufacturing, a production method that offers many advantages, from delivering custom designs without the error of soldering to the use of new base materials that make new designs possible, with easier handling, installation and transportation.

Reel-to-reel production

Multiple advantages. New opportunities.



Endless products possible without error-prone soldering



New base materials such as PET, polyimide, paper etc.



Fast and automated processing on large production lines



Less residual material due to the processing of large roll lengths



Easier handling and installation thanks to self-adhesive backside



Savings potentials in logistics and warehousing



Design advantages in comparison to rigid boards



Higher functional density: dimensions and weight of components lower

Our professional LED Strips and Modules use LEDs from market leaders

We develop and produce our LED strips at a state of the art facility in Germany, with the highest quality standards and by using only LEDs from market leaders such as Nichia, Samsung or Toshiba.

- **Nichia** is the LED market leader, with over 25% market share and decades of experience. Nichia researchers invented the blue and white LED production technology, also receiving the Nobel Prize for this achievement. Nichia LEDs are the **most efficient** (200 lm / w efficacy), durable (> 100,000 hours) and are also available with unique technologies such as **Optisolis**, CRI98+ natural light spectrum and **Rsp0a**, special white light for horticulture.
- **Samsung** is in the top 10 of global LED manufacturers and a well-known brand, renowned for the high performance of its products combined with the competitive price
- **Toshiba** is a Japanese conglomerate with a history of more than a century, now specialized in semiconductors, electronics and hardware, with nearly 20,000 employees and an annual turnover of 40 billion USD. Toshiba has built the TRI-R technology and built the LED chips used in **SunLike CRI97+ LEDs** produced by Seoul Semiconductor in South Korea. With the new **SunLike™ TRI-R™** technology from Toshiba-SSC (Seoul Semiconductor) and our strips and modules you can always enjoy a natural light source with the light spectrum very close to the sun.
- **Seoul Semiconductor** is in the top 10 of global LED manufacturers and renowned for innovation, durability and competitive price

Our strips have high quality components and professional support:

- We use LEDs from top brands and have superior designs
- We offer **professional support** for lighting projects
- The PCBs use high quality materials for best resistance, current flow and heat transfer
- Performance values in this datasheet match those in real world applications
- Function perfectly at high temperatures that would destroy many other strips

CONNECTION OF LED STRIP

The Professional LED Strips are connected via a lead connection to the connection pads provided for this purpose.

For easy connection the following accessories are provided (purchased separately):



15 cm connecting
cable for LumiFlex-
RGBW LED Strips
(SKU 40201)



Direct connecting
cable for LumiFlex-
RGBW LED Strips
(SKU 40204)




15 cm connecting
cable for LumiFlex-
RGBW LED Strips
(SKU 40203)




200 cm connecting
cable for LumiFlex-
RGBW LED Strips
(SKU 40202)

CUTTING INFO



The LED strip can be separated or shortened every 100 mm. On the back of the LED strip is a double-sided heat-conducting adhesive tape, which allows installation of the LED strip. Professional LED strips can be cut with scissors.

LED STRIP PRODUCT NAME EXPLAINED



Due to the special conditions in the production process of LEDs, the specified values are statistical averages. The individual LED may deviate from them.

The LED modules and all their components must not be mechanically stressed.

Avoid undue claw action, e.g. by screwing or excessive bending.

The LED modules must not come into contact with aggressive chemical substances, either in operation or in storage.

The installation of the module (with the operating device) must be carried out in compliance with all applicable electrical and safety standards.

Pay attention to standard ESD precautions when installing the modules.

- The components on the LED modules must not be subjected to mechanical stress.
- The conductive paths on the boards must not be damaged or interrupted by the installation.
- Store and operate the LED modules only at a final humidity of 10% to 60%.

Our LED modules are not protected against overload, overtemperature and short-circuit currents. To operate the modules safely and reliably, it is therefore necessary to use an electronically stabilized power supply unit in which these

in which these safety functions are already integrated. If other power supplies than the ones distributed by us are used, the following protective

the following protective measures must be ensured on the power supply side:

MINIMUM REQUIREMENTS FOR POWER SUPPLIES: Short circuit protection - Overload protection - Overtemperature protection - The installation of LED modules may only be carried out in compliance with all applicable regulations and standards by an authorized electrician.

Distribution and reproduction of this document, utilization and communication of its contents are prohibited unless expressly permitted. Any infringement will result in compensation for damages. All rights reserved in the event of patent, utility model or design registration. We reserve the right to make technical changes.



LUMIFLEX-RGBW-2080 OSRAM LED STRIP RGB-WHITE 5580LM 24V 120 LEDS/M 5M REEL

This LED strip can be purchased via the following websites:

www.ledrise.eu / www.lumistrips.com

