



— PRODUCT DATA SHEET


P3R



P3R

SPECIFICATIONS

TIMELINE



TECHNICAL DATA

Length defocused [mm]	102
Length focused [mm]	106
Head diameter [mm]	20
Tube diameter [mm]	16
Weight incl. batteries [g]	42
Weight without batteries [g]	32
Focus function	Yes
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	No

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery description	10440 3.7V
Total battery voltage [V]	3.7
Total battery capacity [mAh]	320
Total battery energy ² [Wh]	1.184
Rechargeable	Yes
Charging time ⁵ [min]	150
Charging technology	External
Energy modes	Energy Saving
Energy status indicator	Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

IP class	IPX4
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Power

LIGHT SOURCE

Amount LEDs	1
LED type	Power LED
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	65

LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]		140		20
Beam distance ¹ [m]		100		40
Run time ¹ [h]		2.5		6

SWITCH

End Cap Switch

TECHNOLOGIES

Advanced Focus System³, Rapid Focus, Temperature Control System

7
YEAR
WARRANTY⁴



LEDLENSER