




Pendant Luminaires | 220-240 V | topLED 96 W 1800 mA | DALI | CRI 90
7788N



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	96 W
Luminous flux (source)	13965 lm
Frequency	60 - 50 Hz
CCT / Tonalità	4000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	11.2 Kg

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	Iron
Colour	embossed white RAL 9003
Processing	Coating



Pendant Luminaires | 220-240 V | topLED 96 W 1800 mA | DALI | CRI 90
7788N

Single emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 108 topped LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 13965 lm, with a 145.5 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 11.2 kg. The power supply driver is included in the delivery.

The total absorbed power is 96 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	13965 lm
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20 80H