LEDVANCE

PRODUCT DATASHEET
ENDURA STYLE Ellipse 500 13 W DG

ENDURA STYLE ELLIPSE | Decorative and very bright luminaires

AREAS OF APPLICATION

– Outdoor use (IP44)
– Gardens, balconies and other outdoor areas
– Building facades
– Pathway lighting
– Driveways

PRODUCT BENEFITS

– Energy-efficient thanks to LED technology
– Easy and quick installation

PRODUCT FEATURES

– Very bright and functional outdoor LED luminaires
– Die-cast aluminum housing
– Available as wall and bollard luminaires

TECHNICAL DATA

Electrical data

Nominal wattage	12.50 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	>80
Light color (designation)	Warm White
Luminous flux	890 lm

Dimensions & weight

Length	75.0 mm
Width	186.0 mm
Height	500.0 mm
Product weight	2000.00 g

Colors & materials

Body material	Aluminum
Housing color	Dark gray
Product color	Dark gray
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...40 °C

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075205093	Folding carton box 1	84 mm x 194 mm x 521 mm	2180.00 g	8.49 dm³
4058075205109	Shipping carton box 2	205 mm x 185 mm x 540 mm	4597.00 g	20.48 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.