

PRODUCT DATASHEETSST CLAS P DIM 40 DIM 6 W/827 E14 CS

LED SUPERSTAR CLASSIC P | Dimmable LED lamps, classic mini-ball shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

PRODUCT FEATURES

- LED alternative to conventional lamps
- Good quality of light; color rendering index R_a : ≥ 80 ; constant chromaticity
- High color consistency: ≤ 6 SDCM
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Rated wattage	6.00 W	
Nominal wattage	6.00 W	
Nominal voltage	220240 V	
Operating frequency	5060 Hz	
Power factor λ	> 0.80	
Claimed equiv. conventional lamp power	40 W	


Photometrical data

Rated luminous flux	470 lm
Rated color temperature	2700 K
Color rendering index Ra	≥80
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	470 lm

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	80.0 mm
Diameter	45.0 mm
Outer bulb	P45
Length	80.0 mm

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E14
Mercury-free	Yes
Design / version	Frosted
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Mercury content	0.0 mg

Capabilities

|--|

 $^{^{1)}\,\}mathrm{With}$ many common dimmers, see also www.ledvance.com/dim


Certificates & standards

Energy efficiency class	A+		
Energy consumption	6 kWh/1000h		

Country specific categorizations

ILCOS	DRBP/F-6,2-220-240-E14-43/89	
Order reference	LEDSCLP40D 6W/8	

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899900905	SST CLAS P DIM 40 DIM 6 W/827 E14 CS	Shipping carton box 6	274 mm x 72 mm x 133 mm	2.62 dm ³	522.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.